

Phone: 9217 2277 Email: publichealth@whittlesea.vic.gov.au
TTY: 133 677 - ask for 9217 2170 Mail: Locked bag 1 Bundoora MDC 3083

Fax: 9409 9863 Council offices: 25 Ferres Boulevard, South Morang

Please use this form to apply to the City of Whittlesea for a permit to install or alter a septic system. Where tick boxes (\Box) appear please tick where applicable.

Office use only	Issued:	Rec'd:		EHO:	Auth ref:		
Site address for proposed installation/alteration							
Street address Suburb & postcode							
• •	This application is for:						
	s to an existing sys				f a new system		
	Owner details						
Title	First name		Surna	me			
Postal addres	SS			Suburb & pos	stcode		
Contact numb	oore						
	Dels		labila				
Business		IV	lobile				
Email							
	Ow	ner dec	larat	tion			
I hereby apply for permission to have a septic system installed/altered by a registered plumber and drainer. I acknowledge the following constraints apply to the area of land dedicated for the disposal/treatment of septic effluent: No vehicular traffic No access by livestock such as horses and cattle No construction of driveways, footpaths, swimming pools or sheds No access with plastic or play I approve of the location and system proposed in this application.							
Owner signature Date							
				D D M	M Y Y Y Y		
Plumber							
Title	First name		Surna	me			
Street addres	s			Suburb & pos	stcode		
Contact number Licence number							
Mobile							
Email							

Drainer Drainer					
Title First name	Surname				
Street address	Suburb & postcode				
Contact number	Licence number				
Mobile					
Email					
Applicant making an applicat	tion as agent of the owner				
Title First name	Surname				
Ctroot addrsos	Cuburb 9 postoodo				
Street address	Suburb & postcode				
Contact numbers					
Business	Mobile				
Email					
Licence number					
I hereby apply for permission to install/alter a septic sy Signature	stem and supply the following information Date				
	D D M M Y Y Y				
Building o	letails				
Type of Building (House, Factory, Office, Short					
, the contraction of the contrac					
	Number of people expected to use the system per day				
Number of bedrooms (including studies)	per day				
First was to be inc	atallad/altanad				
Fixtures to be ins					
Please provide number of fixtures for each item					
Water closets Basins	Showers Dishwashers				
Baths	Spa bath (capacity in litres)				
Troughs	Waste disposal units				
Other (specify):					

Proposed system components						
	Sewer system drains (external)	☐ Surface irrigation				
	Septic tank	☐ Inspection chamber				
	Sandfilter	☐ Pump well				
	Effluent lines (specify length and width)					
	Sewage treatment plant (specify)					
	Other (specify)					
•	ermit fee is required with this application and a ease check with Council's Health Department if					
	Permit for installation or alteration of an existing septic system					
	□ Sand analysis for Sand Filters (if applicable)					
	□ Packaged sewage treatment plants					
	☐ Subsurface/surface irrigation					
Office use only Date D M M Y Y Receipt no.						
Amo	unt \$ Permit no.					

Effluent distribution

A distribution box constructed of concrete shall be installed following all septic tanks. The distance between the septic tank and distribution box shall be governed by the fall and distance to the disposal/treatment area, but in no case shall be less than one metre. A concrete distribution box is to be located at the start of each effluent line.

The invert of the outlet of the septic tank is to be higher than the ground level at the distribution pit of the first trench.

The minimum internal dimension of the box shall be 250mm. The inlet shall be 50mm above the outlets with a shallow sump provided. All outlets are to be at the same elevation and are to be mortared both internally and externally.

The connecting pipe between the septic tank and the distribution box may comprise 90mm. UPVC in lieu of 100mm sewer UPVC providing at least 300mm of soil cover is provided and the pipe is sleeved in 100mm concrete pipe or 100mm sewer UPVC packed in screenings, where it passes between roadways or trafficable areas.

Plans and specifications

Applications for permits to install a system shall be accompanied by two sets of plans drawn to scale and specifications including the following details:

- A block plan showing the location of the premises.
- A house floor plan including the direction of north and the street and lot number
- A block plan showing contours, the relative position of the proposed septic tank and system and all existing and proposed buildings, driveways, easements, streams and underground water tanks and wells.
- Details including a plan of the proposed septic tank system to be used, showing distances from boundaries, buildings and driveways.
- The existing or proposed position of stormwater drains, water supply pipes, underground power lines, Telecom cables, gas pipes and any other services.
- The measures proposed to intercept and divert drainage away from any disposal area.

- Details and layout of effluent disposal trenches, sand filter or proposed disposal system.
- A summary of the data from which the capacity of the septic system has been computed, such as contributory population, percolation rate of the soil, dosage rates or design factors used for non-standard applications.

Pump installation

- Pumps shall be submersible, automatic, electric, and self-priming, and shall be installed to the regulation of the local electrical authority.
- All electric wiring shall be installed by a registered electrical contractor and shall be inspected and approved by the electricity authority prior to use.
- Pumps must be firmly based on a cement block or bricks so as to be at least 80mm off the floor of the chamber.
- Suction and discharge pipes must be 25mm minimum size, PVC pipe connected to the pump in such a manner as to effect easy disconnection. A non-return valve shall be provided in the riser close to the pump.
- All changes in direction of discharge pipes shall be made by bend (not elbows) and a union provided near the top of the chamber.
- All pump chambers shall be fitted with a float switch operated alarm which shall be triggered in case of pump failure. A large distribution box is required on all pump installations

Required length of effluent lines

Throughout the City of Whittlesea the required length of effluent lines based on the current EPA code of practice is as follows:

(eg) 3 Bedroom House (a study or family room which could be used as a bedroom are also included) All waste septic tank 3200 litres followed by: 120metres of 1m wide effluent line (water reduction fixtures and fittings)
145 metres of 1m wide effluent line (standard water fixtures)

(eg) 4 Bedroom House
All waste septic tank 3200 litres following by:

150 metres of 1m wide effluent line (water reduction fixtures and fittings)
180 metres of 1m wide effluent line (standard water fixtures)

(eg) 5 Bedroom House
All waste septic tank 4500 litres followed by:

180 metres of 1m wide effluent line (water reduction fixtures and fittings)
220 metres of 1m wide effluent line (standard water fixtures)

Subject to a suitable Land Capability Assessment (LCA), variations in effluent trench may be considered.

Details as requested on application must be shown	n on plan
Applicant:	-
Address:	
Contractor:	
Location of job:	

REAR OF ALLOTMENT

REAR OF ALLOTHERS								
1:500	10	20	30	40	50	60	70	80
1:200	4	8	12	16	20	24	28	32
								LEGEND
44								CIP
								Cast Iron Pipe
								DB
								Distribution Box
40								DP
								Down Pipe
								DG
36								Disconnector Gully
30								E.J.
								Expansion Joint
								D.S.V.
32								Downstream Vent
								U.S.V.
								Upstream Vent
								IO
28								Inspection Opening
								ORG
								Overflow Relief
								PPD
24								Plastic Pipe Drain
								SPD
								Stoneware Pipe
								ST
20								Septic Tank
								GI
	+ +							Grease Interceptor
								SWD Starrayatar Drain
16								Stormwater Drain I-C
								Inspection
12								
								Fall of Land
								Fall Of Laffu
8								
								North Point
								1401 till 1 ollit
4								1:200 or <u>1:500</u>
								each square
0								2m-2m
1:200								5m-5m
<u> </u>	· · · · · · · · · · · · · · · · · · ·	·	 	 		1 1	1	

FRONT OF ALLOTMENT